



557 829

(43) International Publication Date
2 December 2004 (02.12.2004)

PCT

(10) International Publication Number
WO 2004/104615 A1

(51) International Patent Classification⁷: **G01R 33/3873**

(21) International Application Number:
PCT/EP2004/005513

(22) International Filing Date: 21 May 2004 (21.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03 136 672.4 23 May 2003 (23.05.2003) CN

(71) Applicant (for all designated States except US):
SIEMENS AKTIENGESELLSCHAFT [DE/DE];
Wittelsbacherplatz 2, 80333 München (DE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **NI, Cheng** [CN/CN];
Flat 401, Block 17, Area 36, 3 Wen Hua Road, Shenzhen

518057 (CN). **XUE, Ting Qiang** [CN/CN]; 17-11A Wei
Lan Hai An, Hou Hai Ave. Nan Shan District, Shenzhen
518054 (CN).


(74) Common Representative: **SIEMENS AKTIENGE-
SELLSCHAFT**; Postfach 22 16 34, 80506 München
(DE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: **MRI MAGNET DEVICE WITH AXIALLY ADJUSTABLE ROSE SHIM RING**



(57) Abstract: This invention relates to a static magnetic field generating device in a MRI equipment, comprising an additional shimming ring on the external edge of the first shimming ring whereby the distance between the first shimming ring and the additional shimming ring is adjustable in the direction parallel to the static magnetic field such as to improve homogeneity of the static magnetic field; a per-manent magnetic source composed of a plurality of permanent magnetic columns with different magnetic energy levels wherein the magnetic energy levels of the external columns are higher than the magnetic energy levels of the columns which are closer to the center of the respective pole; a plurality of magnetic inducing bolts or permanent magnetic bolts; the second shimming ring, the permanent magnetic source and the magnetic inducing bolts or permanent magnetic bolts could be applied jointly.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.